


TSM-DC80.08 TSM-DA80.08

THE **Quadmax** SOLUTION

by **TrinaSolar**



16.4%
MAX EFFICIENCY

210W
MAX POWER OUTPUT

10 YEAR
PRODUCT WARRANTY

25 YEAR
LINEAR POWER WARRANTY

Founded in 1997, Trina Solar (NYSE: TSL) has established itself as a leader in the solar community with its vertically integrated business model. Our modules and system solutions provide clean solar power in on-grid and off-grid residential, commercial, industrial and utility-scale systems.

With more than 22 offices worldwide, Trina Solar has partnerships with leading installers, distributors, utilities and developers in all major PV markets. Trina Solar is committed to driving smarter energy choices.

Trina Solar Limited
www.trinasolar.com

TrinaSolar
Smart Energy Together



Module can bear snow loads up to **5400Pa** and wind loads up to **2400Pa**



Guaranteed power output **0~+3%**



High performance under low light conditions
Cloudy days, mornings and evenings



Modules using Quadmax technology have up to **8%** more power output



Manufactured according to International Quality and Environment Management System Standards **ISO9001, ISO14001**




Black frame improves **aesthetics**



MC4 photovoltaic connectors increase system reliability



LINEAR PERFORMANCE WARRANTY

10 Year Product Warranty • 25 Year Linear Power Warranty




TSM-DC80.08 / TSM-DA80.08 THE **Quadmax** SOLUTION

DIMENSIONS OF PV MODULE TSM-DC/DA80.08



I-V CURVES OF PV MODULE TSM-205 DC/DA80.08



Average efficiency reduction of 4.5% at 200W/m² according to EN 60904-1.

CERTIFICATION




ELECTRICAL DATA @ STC	TSM-195 DC/DA80.08	TSM-200 DC/DA80.08	TSM-205 DC/DA80.08	TSM-210 DC/DA80.08
Peak Power Watts-P _{MAX} (Wp)	195	200	205	210
Power Output Tolerance-P _{MAX} (%)	0/+3	0/+3	0/+3	0/+3
Maximum Power Voltage-V _{MP} (V)	36.7	37.1	37.7	38.3
Maximum Power Current-I _{MPP} (A)	5.31	5.39	5.43	5.48
Open Circuit Voltage-V _{OC} (V)	45.4	45.7	46.2	46.6
Short Circuit Current-I _{SC} (A)	5.70	5.77	5.83	5.88
Module Efficiency η _m (%)	15.2	15.6	16.0	16.4

Values at Standard Test Conditions STC (Air Mass AM1.5, Irradiance 1000W/m², Cell Temperature 25°C). Power measurement tolerance: ±3%

ELECTRICAL DATA @ NOCT	TSM-195 DC/DA80.08	TSM-200 DC/DA80.08	TSM-205 DC/DA80.08	TSM-210 DC/DA80.08
Maximum Power-P _{MAX} (Wp)	144	147	151	155
Maximum Power Voltage-V _{MP} (V)	33.6	34.0	34.6	34.9
Maximum Power Current-I _{MPP} (A)	4.27	4.33	4.35	4.42
Open Circuit Voltage (V)-V _{OC} (V)	42.0	42.2	42.7	43.0
Short Circuit Current (A)-I _{SC} (A)	4.60	4.65	4.66	4.74

NOCT: Irradiance at 800W/m², Ambient Temperature 20°C, Wind Speed 1m/s. Power measurement tolerance: ±3%

MECHANICAL DATA

Solar cells	Monocrystalline 125 × 125mm (5 inches)
Cell orientation	72 cells (6 × 12)
Module dimensions	1581 × 809 × 35mm (62.24 × 31.85 × 1.37 inches)
Weight	14.9kg (32.8 lb)
Glass	High transparency solar glass 3.2mm (0.13 inches)
Frame	Anodized aluminium alloy
J-Box	IP 65 rated
Cables	Photovoltaic Technology cable 4.0mm ² (0.006 inches ²), 900mm (35.4 inches)
Connector	Original MC4 

TEMPERATURE RATINGS

Nominal Operating Cell Temperature (NOCT)	45°C (±2°C)
Temperature Coefficient of P _{MAX}	-0.39%/°C
Temperature Coefficient of V _{OC}	-0.30%/°C
Temperature Coefficient of I _{SC}	0.040%/°C

MAXIMUM RATINGS

Operational Temperature	-40~+85°C
Maximum System Voltage	1000V DC(IEC)/600V DC(UL)
Max Series Fuse Rating	10A

WARRANTY

10 year Product Workmanship Warranty

25 year Linear Power Warranty

(Please refer to product warranty for details)

PACKAGING CONFIGURATION

Modules per box: 29 pieces

Modules per 40' container: 812 pieces