



*Transparent double-glass module can be provided upon request.

DOUBLE-GLASS MODULE







DYMOND CS6X-330 | 335 | 340M-FG

Canadian Solar's Dymond CS6X-M-FG module is a 72 cell double-glass module. By replacing the traditional polymer backsheet with heat-strengthened glass, the Dymond module has a lower annual power degradation than a traditional module and better protection against the elements, making it more reliable and durable during its lifetime.

30
years
power output warranty

10
years
product warranty on materials
and workmanship

KEY FEATURES

-  Up to IEC1500 V_{DC} system voltage, saving on BoS cost
-  Minimizes micro-cracks and prevents snail trails
-  20 % more energy generation
-  Suitable for harsh environments, such as coasts, deserts and lakes
-  Fire Class A certified according to IEC 61730-2 / MST 23
-  5400 Pa snow load, 2400 Pa wind load

MANAGEMENT SYSTEM CERTIFICATES*

ISO 9001:2008 / Quality management system
 ISO 14001:2004 / Standards for environmental management system
 OHSAS 18001:2007 / International standards for occupational health & safety

PRODUCT CERTIFICATES*

IEC 61215 / IEC 61730: VDE / CE / MCS / CEC AU / INMETRO
 UL 1703: CSA / IEC 61701 ED2: VDE
 UL 1703 / IEC 61215 performance: CEC listed (US)
 IEC 60068-2-68: SGS
 Take-e-way



* Please contact your local Canadian Solar sales representative for the specific product certificates applicable in your market.


CANADIAN SOLAR INC. is committed to providing high quality solar products, solar system solutions and services to customers around the world. As a leading PV project developer and manufacturer of solar modules with over 20 GW deployed around the world since 2001, Canadian Solar Inc. (NASDAQ: CSIQ) is one of the most bankable solar companies worldwide.

CANADIAN SOLAR INC.


545 Speedvale Avenue West, Guelph, Ontario N1K 1E6, Canada, www.canadiansolar.com, support@canadiansolar.com

ENGINEERING DRAWING (mm)

Rear View



Corner Protector Detail



ELECTRICAL DATA | STC*

CS6X	330M-FG	335M-FG	340M-FG
Nominal Max. Power (Pmax)	330 W	335 W	340 W
Opt. Operating Voltage (Vmp)	37.5 V	37.8 V	37.9 V
Opt. Operating Current (Imp)	8.80 A	8.87 A	8.97 A
Open Circuit Voltage (Voc)	45.9 V	46.1 V	46.2 V
Short Circuit Current (Isc)	9.31 A	9.41 A	9.48 A
Module Efficiency	16.90%	17.16%	17.42%
Operating Temperature	-40°C ~ +85°C		
Max. System Voltage	1500 (IEC) or 1000 V (UL)		
Module Fire Performance	CLASS A (IEC 61730)		
Max. Series Fuse Rating	15 A		
Application Classification	Class A		
Power Tolerance	0 ~ + 5 W		

* Under Standard Test Conditions (STC) of irradiance of 1000 W/m², spectrum AM 1.5 and cell temperature of 25°C.

ELECTRICAL DATA | NMOT*

CS6X	330M-FG	335M-FG	340M-FG
Nominal Max. Power (Pmax)	242 W	246 W	250 W
Opt. Operating Voltage (Vmp)	34.5 V	34.8 V	34.9 V
Opt. Operating Current (Imp)	7.03 A	7.08 A	7.16 A
Open Circuit Voltage (Voc)	42.7 V	42.9 V	43.0 V
Short Circuit Current (Isc)	7.52 A	7.60 A	7.66 A

* Under Nominal Module Operating Temperature (NMOT), irradiance of 800 W/m², spectrum AM 1.5, ambient temperature 20°C, wind speed 1 m/s.


PERFORMANCE AT LOW IRRADIANCE

Outstanding performance at low irradiance, with an average relative efficiency of 96.5 % for irradiances between 200 W/m² and 1000 W/m² (AM 1.5, 25°C).

The aforesaid datasheet only provides the general information on Canadian Solar products and, due to the on-going innovation and improvement, please always contact your local Canadian Solar sales representative for the updated information on specifications, key features and certification requirements of Canadian Solar products in your region.

Please be kindly advised that PV modules should be handled and installed by qualified people who have professional skills and please carefully read the safety and installation instructions before using our PV modules.

CS6X-335M-FG / I-V CURVES



MECHANICAL DATA

Specification	Data
Cell Type	Mono-crystalline, 6 inch
Cell Arrangement	72 (6 × 12)
Dimensions	1968×992×5.8mm (77.5×39.1×0.23 in) without J-Box and corner protector
(Incl. corner protector)	1972×996×8.5 mm (77.6×39.2×0.33 in) without J-Box
Weight	27.5 kg (60.6 lbs)
Front / Back Glass	2.5 mm heat strengthened glass
Frame	Frameless
J-Box	Split J-Box, IP67, 3 diodes
Cable	4 mm ² (IEC) or 4 mm ² & 12 AWG 1000 V (UL)
Cable Length	1150 mm (45.3 in), 500 mm (19.7 in) (+) and 350 mm (13.8 in) (-) is optional for portrait installation*
Connectors	T4 series or MC4 series or UTX(IEC1500V), T4 series or 05-6 (UL1000V)
Per Pallet	30 pieces, 930kg (2050.3lbs)
Per Container (40' HQ)	660 pieces

* The application of this short length cable can only be used in landscape installation (clamping mounting method) systems in which the distance between modules should be less than or equal to 50 mm. In the event the distance between the PV modules to be installed is more than 50 mm, please make sure to consult our technical team for evaluation and advice.

TEMPERATURE CHARACTERISTICS

Specification	Data
Temperature Coefficient (Pmax)	-0.41 % / °C
Temperature Coefficient (Voc)	-0.31 % / °C
Temperature Coefficient (Isc)	0.053 % / °C
Nominal Module Operating Temperature (NMOT)	43±2 °C

PARTNER SECTION

